



333 SK

Side knife attachment

Global® SK Series - Single needle lockstitch with edge cutter

TECHNICAL SPECIFICATIONS

Machine speed*
4500 spm

Number of needles
1

Stitch type
301

Stitch length
0-5 mm

Presser foot lift
by hand: 4 mm
by knee: 10 mm

Needle type
DBx1

Needle bar stroke
31,8 mm

Standard cutting width
4,8 mm

Electric presser foot lift
optional

333 SK - Single needle, drop feed lockstitch machine with edge cutter. Machine has fully automatic lubrication.

NF 331 SK - Same as above, but with needle feed.

NF 331 SK-AUT - Same as NF 331 SK, but with thread trimmer and automatic back tack.

UNA AGUJA CON RECORTE LATERAL

333 SK - Máquina de pespunte, una aguja, arrastre por diente con recorte lateral (coser y cortar).
Lubrificación automática.

NF 331 SK - La misma que la 333 SK, pero equipada con arrastre aguja.

NF 331 SK-AUT - La misma que la NF 331 SK, pero equipada con corta-hilos y remate eléctrico.

EINNADELMASCHINE MIT KANTENBESCHNEIDUNG

333 SK - Einnadel, Untertransport, Steppstich, Schnellnäher mit Kantenabschneider. Die Maschine ist mit vollautomatischer Schmierung ausgestattet.

NF 331 SK - Baugleich mit 333 SK, jedoch mit Nadeltransport.

NF 331 SK-AUT - Baugleich mit NF 331 SK, jedoch mit Fadenabschneider und Verriegelungsautomatik (elektrisch).

MACHINE UNE AIGUILLE AVEC COUPEAU RASEUR

333 SK - Machine une aiguille point noué, entraînement par griffe, avec couteau raseur.
Lubrification automatique.

NF 331 SK - Identique au modèle 333 SK, mais avec entraînement aiguille.

NF 331 SK-AUT - Identique au modèle NF 331 SK, mais avec coupe-filet arrêts automatiques.

★ Max. sewing speed (in spm.) depends on type of operation and/or materials to be sewn.

The GLOBAL® Selection is brought to you by:

GLOBAL® is a trademark of the Global International Corporation, the people that carefully organize the supply of spareparts before they launch each product.

When ordering parts please specify:

[1] machine model

[2] part numbers