



Global[®] BT 5040 Series - Electronic pattern / labelling machine

TECHNICAL SPECIFICATIONS

Machine speed*

Max 2400 spm

Stitch length

0,1 - 10 mm

Feeding system

By pulse motor (X-Y)

Sewing range

50 x 40 mm

Hook type

Standard shuttle hook

Needle type

Standard shuttle hook

Needle type

DP x 17

Presser foot lift

Up to 20 mm

(pneumatic)

Power source

240 v - 1 phase

50 - 60 Hz direct drive

AC servo motor

Bed type

cylinder

BT 5040 – This machine is driven by a direct drive AC servo motor and is suitable to sew medium / heavy materials. Pattern programmable on control panel. Complete with table top, stand and motor

MÁQUINA ELECTRÓNICA DE PATRONES DE ADORNO

BT 5040 – Máquina accionada por un motor AC servo directo, adecuada para coser materiales medios y pesados. Patrones programable en el panel de control. Estandar la máquina se suministra complete con bancada, tablero y motor.

ELEKTRONISCHER STICH MUSTERRIEGELMASCHINE

BT 5040 – Diese Maschine wird angetrieben durch einem integriertem AC-Servomotor und ist geeignet für mittlere und schwere materialen. Stichbildern programmierbar auf Kontrollbereich. Komplet mit Tisch und Servomotor.

MACHINE ARRÊT À COMMANDE ÉLECTRONIQUE

BT 5040 – Machine à commande par moteur servo AC et compatible pour la couture de matières mi-lourde à Lourdes. Programmes programmable sur le panneau de commande. Livrée complète avec bati, table et moteur AC.

★ Max. sewing speed (in spm.) depends on type of operation and/or materials to be sewn.

The GLOBAL[®] Selection is brought to you by:

GLOBAL[®] is a trademark of the Global International Corporation, the people that carefully organize the supply of spareparts before they launch each product.

When ordering parts please specify:

- 1 machine model
- 2 part numbers